

F2H-FTB-2-A Fiber Termination Box-2 Cores



Description:

Grandway's Fiber Termination Box provides a high density wall mounted solution for next generation networks, which aims to provide and manage maximum numbers of fiber termination in a limited space. It is normally installed in the way of wall mounting.

Features:

- 1. Water-proof design with IP65 Protection level
- 2. Integrated with splice cassette and cable management system
- 3. Manage fibers in a reasonable fiber radius condition
- 4. Easy to maintain and extend the capacity
- 5. Fiber bend radius control more than 40mm
- 6. Suitable for the fusion splice or mechanical splice
- 7. 2 ports cable entrance for FTTH drop cable

Configuration:

Material	Size	Max Capacity		Empty Weight	Loaded Weight	Color
PC+ABS	A*B*C(mm)	SC	LC	0.01	0.9kg	White
	102*167*31	2 Ports	4 Ports	0.6kg		

How to order a Grandway Fiber Termination Box?



Model Rules: F2H-FTB-2-A-XX-XX

Model	Capacity	Туре	XX: Adapter	XX: Pigtail
		A	SC: SC/UPC	SC: SC/UPC
ETD	2		AS: SC/APC	AS: SC/APC
FTB	2		LC: LC/UPC	LC: LC/UPC
			AL: LC/APC	AL: LC/APC