

Slidable Rack-mount Fiber Optic Patch Panel

(FOA-ACC-DIO-24P-1UE)

Slidable Rack-mount Fiber Optic Distribution Frame has cold steel sliding fittings with self-locking functions prevent the drawer from falling when moved; 19-inch rack mount for ST, SC, LC,, FC adapters. The drawer is the holding board for splicing, easy to withdraw the fibers when testing and distributing.

ITB/NR-SC



ITB/NR-SC24



ITB/RS-LC48



Specification:

Features:

- Standard size, light weight and reasonable structure
- Slide out drawer for easy cable management
- Suitable for ribbon and single fiber
- Compact design for space saving
- Various panel plate to fit different adapter interface
- Front mark on the plate is easy for identification and operation
- Easy for management and operation

Application:

Telecommunications subscriber loop Fiber to the home (FTTH) LAN/WAN CATV

Model	Fiber Quantity	Height	Dimension(mm)	Weight(Kg)
ITB/NR-SC6	6	1U	430x 200x44.5	3.45
ITB/NR-2SC6	12	1U	430*200*44.5	3.5
ITB/NR-SC12	12	1U	430x 200x44.5	3.5
ITB/NR-2SC12	24	1U	430x 200x44.5	3.6
ITB/NR-SC24	24	1U	430x 200x44.5	3.6
ITB/NR-2SC24	48	1U	430x 200x44.5	3.9
ITB/NR-SC48	48	2U	430x200x89	6.2
ITB/NR-2SC48	96	2U	430x200x89	6.5
ITB/NR-SC72	72	4U	430x200x178	8.7



Panel size:

