



F2H-LFC Launch Fiber Cable

- Compact and ruggedized, easy to carry
- Excellent waterproof and dustproof performance
- Non-metal construction will not corrode or conduct electricity

Items	Specifications
Dimension	238(L) x 141(W) x 67(H)mm
Fiber Type	G.657A/G.652D (MM can be customized)
Typical Loss	<0.5dB @ 1310nm for 1,000 meters
Connector Type	FC/SC/LC selectable
Polishing Type	APC/UPC selectable
Box Material	Polypropylene
Color	yellow
Weight	0.75kg / 0.35kg (without fiber)
Operating Temperature	-40~+55°C
Ordering Information	
Name	LFC=Launch Fiber Cable
Connector 1	SC=SC/UPC; AS=SC/APC; FC=FC/UPC; AF=FC/APC; LC=LC/UPC; AL=LC/APC
Connector 2	SC=SC/UPC; AS=SC/APC; FC=FC/UPC; AF=FC/APC; LC=LC/UPC; AL=LC/APC
Fiber Type	7A1=SM G.657.A1; 2D=SM G.652.D; OM1=MM 62.5/125um; OM2=MM 50/125um
Cable Length	0.5=0.5km; 1=1km; 2=2km



FHO-LCB Launch Cable Box

- Compact, easy to carry
- Case can house up to 1,000 meters of fiber
- Attachable with FHO5000 Series OTDR

Items	Specifications
Dimension	206(L) x 122(W) x 23(H)mm
Fiber Type	SM G.652D
Adapter Type	Replaceable FC/SC/ST adapters
Polishing Type	APC or UPC
Color	black
Weight	1kg
Operating Temperature	-40~+55°C
Ordering Information	
Name	LCB=Launch Cable Box
Adapter 1	SC=SC/UPC; AS=SC/APC; FC=FC/UPC; AF=FC/APC; ST=ST/UPC; AT=ST/APC;
Adapter 2	SC=SC/UPC; AS=SC/APC; FC=FC/UPC; AF=FC/APC; ST=ST/UPC; AT=ST/APC;
Fiber Type	7A1=SM G.657.A1; 2D=SM G.652.D; OM1=MM 62.5/125um; OM2=MM 50/125um
Cable Length	500=500m; 1000=1000m